



# Efficient Solvers for Some Classes of Time-Periodic Eddy Current Optimal Control Problems

Michael Kolmbauer

Doctoral Program "Computational Mathematics" (W1214)  
Johannes Kepler University  
Altenberger Str. 69, 4040 Linz, Austria

Ulrich Langer

Institute of Computational Mathematics, Johannes Kepler University  
Altenberger Str. 69, 4040 Linz, Austria

NuMa-Report No. 2012-08

November 2012

## Technical Reports before 1998:

### 1995

- 95-1 Hedwig Brandstetter  
*Was ist neu in Fortran 90?* March 1995
- 95-2 G. Haase, B. Heise, M. Kuhn, U. Langer  
*Adaptive Domain Decomposition Methods for Finite and Boundary Element Equations.* August 1995
- 95-3 Joachim Schöberl  
*An Automatic Mesh Generator Using Geometric Rules for Two and Three Space Dimensions.* August 1995

### 1996

- 96-1 Ferdinand Kickingger  
*Automatic Mesh Generation for 3D Objects.* February 1996
- 96-2 Mario Goppold, Gundolf Haase, Bodo Heise und Michael Kuhn  
*Preprocessing in BE/FE Domain Decomposition Methods.* February 1996
- 96-3 Bodo Heise  
*A Mixed Variational Formulation for 3D Magnetostatics and its Finite Element Discretisation.* February 1996
- 96-4 Bodo Heise und Michael Jung  
*Robust Parallel Newton-Multilevel Methods.* February 1996
- 96-5 Ferdinand Kickingger  
*Algebraic Multigrid for Discrete Elliptic Second Order Problems.* February 1996
- 96-6 Bodo Heise  
*A Mixed Variational Formulation for 3D Magnetostatics and its Finite Element Discretisation.* May 1996
- 96-7 Michael Kuhn  
*Benchmarking for Boundary Element Methods.* June 1996

### 1997

- 97-1 Bodo Heise, Michael Kuhn and Ulrich Langer  
*A Mixed Variational Formulation for 3D Magnetostatics in the Space  $H(\text{rot}) \cap H(\text{div})$*  February 1997
- 97-2 Joachim Schöberl  
*Robust Multigrid Preconditioning for Parameter Dependent Problems I: The Stokes-type Case.* June 1997
- 97-3 Ferdinand Kickingger, Sergei V. Nepomnyaschikh, Ralf Pfau, Joachim Schöberl  
*Numerical Estimates of Inequalities in  $H^{\frac{1}{2}}$ .* August 1997
- 97-4 Joachim Schöberl  
*Programmbeschreibung NAOMI 2D und Algebraic Multigrid.* September 1997

From 1998 to 2008 technical reports were published by SFB013. Please see

<http://www.sfb013.uni-linz.ac.at/index.php?id=reports>

From 2004 on reports were also published by RICAM. Please see

<http://www.ricam.oeaw.ac.at/publications/list/>

For a complete list of NuMa reports see

<http://www.numa.uni-linz.ac.at/Publications/List/>

# Efficient solvers for some classes of time-periodic eddy current optimal control problems

Michael Kolmbauer<sup>1</sup> and Ulrich Langer<sup>2</sup>

<sup>1</sup> Johannes Kepler University Linz, DK Computational Mathematics,  
Altenberger Str. 69, 4040 Linz, Austria,  
`kolmbauer@numa.uni-linz.ac.at`

<sup>2</sup> Johannes Kepler University Linz, Institute of Computational Mathematics,  
Altenberger Str. 69, 4040 Linz, Austria,  
`ulanger@numa.uni-linz.ac.at`

**Abstract.** In this paper, we present and discuss the results of our numerical studies of preconditioned MinRes methods for solving the optimality systems arising from the multiharmonic finite element approximations to time-periodic eddy current optimal control problems in different settings including different observation and control regions, different tracking terms as well as box constraints for the Fourier coefficients of the state and the control. These numerical studies confirm the theoretical results published by the first author in a recent paper.

**Keywords:** time-periodic eddy current optimal control problems, multiharmonic finite element discretization, MinRes solver, preconditioners.

## 1 Introduction

This work is devoted to the study of efficient solution procedures for the following time-periodic eddy current optimal control problem: Minimize the functional

$$J(\mathbf{y}, \mathbf{u}) = \frac{1}{2} \int_{\Omega_1 \times (0, T)} |\mathbf{y} - \mathbf{y}_d|^2 d\mathbf{x} dt + \frac{\alpha}{2} \int_{\Omega_1 \times (0, T)} |\mathbf{curl} \mathbf{y} - \mathbf{y}_c|^2 d\mathbf{x} dt + \frac{\lambda}{2} \int_{\Omega_2 \times (0, T)} |\mathbf{u}|^2 d\mathbf{x} dt, \quad (1)$$

subject to the state equations

$$\begin{cases} \sigma \frac{\partial \mathbf{y}}{\partial t} + \mathbf{curl}(\nu \mathbf{curl} \mathbf{y}) = \mathbf{u}, & \text{in } \Omega \times (0, T), \\ \operatorname{div}(\sigma \mathbf{y}) = 0, & \text{in } \Omega \times (0, T), \\ \mathbf{y} \times \mathbf{n} = \mathbf{0}, & \text{on } \partial\Omega \times (0, T), \\ \mathbf{y}(0) = \mathbf{y}(T), & \text{in } \Omega, \end{cases} \quad (2)$$

where  $\Omega$  is a bounded, simply connected Lipschitz domain with the boundary  $\partial\Omega$ . The domains  $\Omega_1$  and  $\Omega_2$  are non-empty Lipschitz subdomains of  $\Omega$ , i.e.,

$\Omega_1, \Omega_2 \subset \Omega \subset \mathbb{R}^3$ . The reluctivity  $\nu \in L^\infty(\Omega)$  and the conductivity  $\sigma \in L^\infty(\Omega)$  are supposed to be uniformly positive, i.e.,

$$0 < \nu_{\min} \leq \nu(\mathbf{x}) \leq \nu_{\max}, \quad \text{and} \quad 0 < \sigma_{\min} \leq \sigma(\mathbf{x}) \leq \sigma_{\max}, \quad \mathbf{x} \in \Omega.$$

We mention that the electric conductivity  $\sigma$  vanishes in regions consisting of non-conducting materials. In order to fulfill the assumption made above on the uniform positivity of  $\sigma$ , one can replace  $\sigma(x)$  by  $\max\{\epsilon, \sigma(x)\}$  with some suitably chosen positive  $\epsilon$ , see, e.g., [10,12] for more details. We here assume that the reluctivity  $\nu$  is independent of  $|\mathbf{curl} \mathbf{y}|$ , i.e. we only consider linear eddy current problems. The regularization parameter  $\lambda > 0$ , the weight parameter  $\alpha \geq 0$ , and  $\mathbf{y}_d, \mathbf{y}_c \in L_2((0, T), \mathbf{L}_2(\Omega))$  are given data, where  $\mathbf{y}_d$  represents the desired state and  $\mathbf{y}_c$  represents the desired **curl** of the state.

The problem setting (1)-(2) has been analyzed in [11,12], wherein, due to the time-periodic structure, a time-discretization in terms of a truncated Fourier series, also called multiharmonic approach, is used. In [12], we consider the special case of a fully distributed optimal control problem for tracking some  $\mathbf{y}_d$  in the complete computational domain, i.e.  $\Omega_1 = \Omega_2 = \Omega$  and  $\alpha = 0$  in (1), whereas [11] is devoted to the various other settings including different observation and control regions, different tracking terms as well as box constraints for the Fourier coefficients of the state and the control. Similar optimal control problems for time-periodic parabolic equations and their numerical treatment by means of the multiharmonic Finite Element Method (FEM) have recently been considered in [9] and [8]. Other approaches to time-periodic parabolic optimal control problems have been discussed in [1]. There are many publications on optimal control problems with PDE constraints given by initial-boundary value problems for parabolic equations, see, e.g., [14] for a comprehensive presentation. There are less publications on optimal control problems where initial-boundary value problems for eddy current equations are considered as PDE constraints, see, e.g., [16,15] where one can also find interesting applications. The multiharmonic approach allows us to switch from the time domain to the frequency domain, and, therefore, to replace a time-dependent problem by a system of time-independent problems for the Fourier coefficients. Since we are here interested in studying robust solvers, this special time-discretization technique justifies the following assumption: Let us assume, that the desired states  $\mathbf{y}_d$  and  $\mathbf{y}_c$  are multiharmonic, i.e.,  $\mathbf{y}_d$  and  $\mathbf{y}_c$  have the form of a truncated Fourier series:

$$\begin{aligned} \mathbf{y}_d &= \sum_{k=0}^N \mathbf{y}_{d,k}^c \cos(k\omega t) + \mathbf{y}_{d,k}^s \sin(k\omega t), \\ \mathbf{y}_c &= \sum_{k=0}^N \mathbf{y}_{c,k}^c \cos(k\omega t) + \mathbf{y}_{c,k}^s \sin(k\omega t). \end{aligned} \tag{3}$$

Consequently, the state  $\mathbf{y}$  and the control  $\mathbf{u}$  are multiharmonic as well, and, therefore, have a representation in terms of a truncated Fourier series with the

same number of modes  $N$ , i.e.,

$$\begin{aligned}\mathbf{y} &= \sum_{k=0}^N \mathbf{y}_k^c \cos(k\omega t) + \mathbf{y}_k^s \sin(k\omega t), \\ \mathbf{u} &= \sum_{k=0}^N \mathbf{u}_k^c \cos(k\omega t) + \mathbf{u}_k^s \sin(k\omega t).\end{aligned}\tag{4}$$

Using the multiharmonic representation of  $\mathbf{y}_d$ ,  $\mathbf{y}_c$ ,  $\mathbf{y}$  and  $\mathbf{u}$ , the minimization problem (1)-(2) can be state in the frequency domain: Minimize the functional

$$\begin{aligned}J_N &= \frac{1}{2} \sum_{k=0}^N \left[ \sum_{j \in \{c,s\}} \left[ \int_{\Omega_1} |\mathbf{y}_k^j - \mathbf{y}_{d,k}^j|^2 dx + \alpha \int_{\Omega_1} |\mathbf{curl} \mathbf{y}_k^j - \mathbf{y}_{c,k}^j|^2 dx \right. \right. \\ &\quad \left. \left. + \lambda \sum_{j \in \{c,s\}} \int_{\Omega_2} |\mathbf{u}_k^j|^2 dx \right] \right],\end{aligned}\tag{5a}$$

subject to the state equation

$$\left\{ \begin{array}{ll} k\omega \sigma \mathbf{y}_k^s + \mathbf{curl}(\nu \mathbf{curl} \mathbf{y}_k^c) = \mathbf{u}_k^c, & \text{in } \Omega, k = 1, \dots, N, \\ -k\omega \sigma \mathbf{y}_k^c + \mathbf{curl}(\nu \mathbf{curl} \mathbf{y}_k^s) = \mathbf{u}_k^s, & \text{in } \Omega, k = 1, \dots, N, \\ \mathbf{curl}(\nu \mathbf{curl} \mathbf{y}_0^c) = \mathbf{u}_0^c, & \text{in } \Omega, \\ \mathbf{y}_k^c \times \mathbf{n} = \mathbf{y}_k^s \times \mathbf{n} = \mathbf{0}, & \text{on } \partial\Omega, k = 1, \dots, N, \\ \mathbf{y}_k^0 \times \mathbf{n} = \mathbf{0}, & \text{on } \partial\Omega, \end{array} \right.\tag{5b}$$

completed by the divergence constraints

$$\left\{ \begin{array}{ll} k\omega \operatorname{div}(\sigma \mathbf{y}_k^c) = 0, & \text{in } \Omega, k = 1, \dots, N, \\ k\omega \operatorname{div}(\sigma \mathbf{y}_k^s) = 0, & \text{in } \Omega, k = 1, \dots, N, \\ \operatorname{div}(\sigma \mathbf{y}_0^c) = 0, & \text{in } \Omega. \end{array} \right.\tag{5c}$$

Additionally, we add control constraints associated to the Fourier coefficients of the control  $\mathbf{u}$ , i.e.

$$\begin{aligned}\underline{\mathbf{u}}_k^c &\leq \mathbf{u}_k^c \leq \overline{\mathbf{u}}_k^c, & \text{a.e. in } \Omega, k = 0, 1, \dots, N, \\ \underline{\mathbf{u}}_k^s &\leq \mathbf{u}_k^s \leq \overline{\mathbf{u}}_k^s, & \text{a.e. in } \Omega, k = 1, \dots, N,\end{aligned}\tag{5d}$$

and state constraints associated to the Fourier coefficients of the state  $\mathbf{y}$ , i.e.

$$\begin{aligned}\underline{\mathbf{y}}_k^c &\leq \mathbf{y}_k^c \leq \overline{\mathbf{y}}_k^c, & \text{a.e. in } \Omega, k = 0, 1, \dots, N, \\ \underline{\mathbf{y}}_k^s &\leq \mathbf{y}_k^s \leq \overline{\mathbf{y}}_k^s, & \text{a.e. in } \Omega, k = 1, \dots, N.\end{aligned}\tag{5e}$$

This minimization problem is typically solved by deriving the corresponding optimality system, which is then discretized in space by means of the FEM. Since even the simple box constraints (5d)-(5e) give rise to nonlinear optimality systems, we apply a primal dual active set strategy (semi-smooth Newton) approach for their solution [5]. The resulting procedure is summarized in Algorithm 1.

**Input:** number of modes  $N$ , initial guesses  $\mathbf{x}^{(k,0)} \in \mathbb{R}^n (k = 0, \dots, N)$ .  
**Output:** approximate solution  $\mathbf{x}^{(k,l)} \in \mathbb{R}^n (k = 0, \dots, N)$ .  
**for**  $k \leftarrow 0$  **to**  $N$  **do**  
    | Determine the active sets  $\mathcal{E}_{k,0}^c$  and  $\mathcal{E}_{k,0}^s$ ;  
**end**  
Set  $l := 0$ ;  
**while** *not converged* **do**  
    **for**  $k \leftarrow 0$  **to**  $N$  **do**  
        | Compute  $\mathbf{b}_{\mathcal{E}}^{(k,l+1)}, \mathcal{A}_{\mathcal{E}}^{(k,l+1)}$ ;  
        | Solve  $\mathcal{A}_{\mathcal{E}}^{(k,l+1)} \mathbf{x}^{(k,l+1)} = \mathbf{b}_{\mathcal{E}}^{(k,l+1)}$ ;  
        | Determine the active sets  $\mathcal{E}_{k,l+1}^c$  and  $\mathcal{E}_{k,l+1}^s$ ;  
    **end**  
    Set  $l := l + 1$ ;  
**end**

**Algorithm 1:** Primal dual active set strategy.

The specific structure of the Jacobi matrix  $\mathcal{A}_{\mathcal{E}}^{(k,l+1)}$  depends on the actual computational setting. In our applications  $\mathcal{A}_{\mathcal{E}}^{(k,l+1)}$  obtains either the form  $\mathcal{A}_1$ , cf. (6a), or the form  $\mathcal{A}_2$ , cf. (6b). It is clear, that the efficient and parameter-robust solution of the  $(N + 1)$  linear systems of equations at each semi-smooth Newton step are essential for the efficiency of the proposed method. For further details we refer to [11].

## 2 Parameter-robust and efficient solution procedures

In order to discretize the problems in space, we use the edge (Nédélec) finite element space  $\mathcal{ND}_0^0(\mathcal{T}_h)$ , that is a conforming finite element subspace of  $\mathbf{H}_0(\mathbf{curl}, \Omega)$ , and the nodal (Lagrange) finite element space  $\mathcal{S}_0^1(\mathcal{T}_h)$ , that is a conforming finite element subspace of  $H_0^1(\Omega)$ . Let  $\{\varphi_i\}_{i=1, N_h}$  and  $\{\psi_i\}_{i=1, M_h}$  denote the usual edge basis of  $\mathcal{ND}_0^0(\mathcal{T}_h)$  and the usual nodal basis of  $\mathcal{S}_0^1(\mathcal{T}_h)$ , respectively. We are now in the position to define the following FEM matrices:

$$\begin{aligned} (\mathbf{K}_{\nu})_{ij} &= (\nu \mathbf{curl} \varphi_i, \mathbf{curl} \varphi_j)_{0, \Omega}, \\ (\mathbf{M}_{\sigma, k\omega})_{ij} &= k\omega (\sigma \varphi_i, \varphi_j)_{0, \Omega}, \\ (\mathbf{M})_{ij} &= (\varphi_i, \varphi_j)_{0, \Omega}, \\ (\mathbf{D}_{\sigma, k\omega})_{ij} &= k\omega (\sigma \varphi_i, \nabla \psi_j)_{0, \Omega}, \end{aligned}$$

where  $(\cdot, \cdot)_{0, \Omega}$  denotes the inner product in  $\mathbf{L}_2(\Omega)$ . Throughout this paper we are repeatedly faced with the following two types of system matrices:

$$\mathcal{A}_1 = \begin{pmatrix} * & \mathbf{0} & \mathbf{K}_{\nu} & -\mathbf{M}_{\sigma, k\omega} \\ \mathbf{0} & * & \mathbf{M}_{\sigma, k\omega} & \mathbf{K}_{\nu} \\ \mathbf{K}_{\nu} & \mathbf{M}_{\sigma, k\omega} & -\lambda^{-1} * & \mathbf{0} \\ -\mathbf{M}_{\sigma, k\omega} & \mathbf{K}_{\nu} & \mathbf{0} & -\lambda^{-1} * \end{pmatrix} \quad (6a)$$

$$\mathcal{A}_2 = \begin{pmatrix} * & \mathbf{0} & \mathbf{K}_\nu & -\mathbf{M}_{\sigma,k\omega} & \mathbf{0} & \mathbf{0} & \mathbf{D}_{\sigma,k\omega}^T & \mathbf{0} \\ \mathbf{0} & * & \mathbf{M}_{\sigma,k\omega} & \mathbf{K}_\nu & \mathbf{0} & \mathbf{0} & \mathbf{0} & \mathbf{D}_{\sigma,k\omega}^T \\ \mathbf{K}_\nu & \mathbf{M}_{\sigma,k\omega} & -\lambda^{-1}* & \mathbf{0} & \mathbf{D}_{\sigma,k\omega}^T & \mathbf{0} & \mathbf{0} & \mathbf{0} \\ -\mathbf{M}_{\sigma,k\omega} & \mathbf{K}_\nu & \mathbf{0} & -\lambda^{-1}* & \mathbf{0} & \mathbf{D}_{\sigma,k\omega}^T & \mathbf{0} & \mathbf{0} \\ \mathbf{0} & \mathbf{0} & \mathbf{D}_{\sigma,k\omega} & \mathbf{0} & \mathbf{0} & \mathbf{0} & \mathbf{0} & \mathbf{0} \\ \mathbf{0} & \mathbf{0} & \mathbf{0} & \mathbf{D}_{\sigma,k\omega} & \mathbf{0} & \mathbf{0} & \mathbf{0} & \mathbf{0} \\ \mathbf{D}_{\sigma,k\omega} & \mathbf{0} & \mathbf{0} & \mathbf{0} & \mathbf{0} & \mathbf{0} & \mathbf{0} & \mathbf{0} \\ \mathbf{0} & \mathbf{D}_{\sigma,k\omega} & \mathbf{0} & \mathbf{0} & \mathbf{0} & \mathbf{0} & \mathbf{0} & \mathbf{0} \end{pmatrix}. \quad (6b)$$

Therein the placeholder  $*$  stands for a symmetric and positive semi-definite matrix, that actually depends on the considered setting, cf. Table 1. The family of problems, that are related with the matrix type  $\mathcal{A}_1$  and  $\mathcal{A}_2$  are referred as *Formulation OC-FEM 1* and *Formulation OC-FEM 2*, respectively. In fact, the system matrix  $\mathcal{A}_1$  and  $\mathcal{A}_2$  are symmetric and indefinite, and obtain a double- or three-fold saddle point structure, respectively. Since  $\mathcal{A}_1$  and  $\mathcal{A}_2$  are symmetric, the corresponding systems can be solved by a preconditioned Minimal Residual (MinRes) method, cf. [13]. Typically, the convergence rate of any iterative Krylov subspace method applied to the unpreconditioned system deteriorates with respect to the meshsize  $h$ , the parameters  $k = 0, 1, \dots, N$  and  $\omega$  involved in the spectral time-discretization, and the problem parameters  $\nu$ ,  $\sigma$  and  $\lambda$ , cf. also Tables 2 and 3. Therefore, preconditioning is an important issue.

The proper choice of parameter-robust and efficient preconditioners has been addressed by the authors in [11,12]. While for equations with system matrices of type (6a), we propose to use the preconditioner

$$\mathcal{C} := \text{diag} \left( \sqrt{\lambda}\mathbf{F}, \sqrt{\lambda}\mathbf{F}, \frac{1}{\sqrt{\lambda}}\mathbf{F}, \frac{1}{\sqrt{\lambda}}\mathbf{F} \right), \quad (7)$$

with the block  $\mathbf{F} = \mathbf{K}_\nu + \mathbf{M}_{\sigma,k\omega} + 1/\sqrt{\lambda}\mathbf{M}$ , for equations with system matrices of type (6b), we advise to use the preconditioner

$$\mathcal{C}_M = \text{diag} \left( \sqrt{\lambda}\mathbf{F}, \sqrt{\lambda}\mathbf{F}, \frac{1}{\sqrt{\lambda}}\mathbf{F}, \frac{1}{\sqrt{\lambda}}\mathbf{F}, \frac{1}{\sqrt{\lambda}}\mathbf{S}_J, \frac{1}{\sqrt{\lambda}}\mathbf{S}_J, \sqrt{\lambda}\mathbf{S}_J, \sqrt{\lambda}\mathbf{S}_J \right), \quad (8)$$

where  $\mathbf{S}_J = \mathbf{D}_{\sigma,k\omega}^T \mathbf{F}^{-1} \mathbf{D}_{\sigma,k\omega}$ . In a MinRes setting, the quality of the preconditioners  $\mathcal{C}$  and  $\mathcal{C}_M$ , used for the system matrices  $\mathcal{A}_1$  and  $\mathcal{A}_2$ , respectively, is in general determined by the condition number  $\kappa_1$  or  $\kappa_2$  of the preconditioned system, defined as follows:

$$\kappa_1 := \|\mathcal{C}^{-1}\mathcal{A}_1\|_{\mathcal{C}} \|\mathcal{A}_1^{-1}\mathcal{C}\|_{\mathcal{C}} \quad \text{and} \quad \kappa_2 := \|\mathcal{C}_M^{-1}\mathcal{A}_2\|_{\mathcal{C}_M} \|\mathcal{A}_2^{-1}\mathcal{C}_M\|_{\mathcal{C}_M}. \quad (9)$$

In Table 1, we list the theoretical results, that have been derived for different settings of (5) in [11,12]. We especially want to point out, that the bounds for the condition numbers are at least uniform in the space discretization parameter  $h$  as well as the time discretization parameters  $\omega$  and  $N$ . This has the important consequence, that the proposed preconditioned MinRes method converges within a few iterations, independent of the discretization parameters that are directly related to the size of the system matrices.

**Table 1.** Condition number estimates for different settings. Here  $(\sigma)$  denotes robustness with respect to  $\sigma \in \mathbb{R}^+$ .

	parameters	domains	equations	condition number estimate
I	$\alpha = 0$	$\Omega_1 = \Omega_2$	(5a)-(5b)	$\kappa_1 \leq \sqrt{3} \neq c(h, \omega, N, \sigma, \nu, \lambda)$
II	$\alpha = 0$	$\Omega_1 = \Omega_2$	(5a)-(5c)	$\kappa_2 \leq \sqrt{3}(1 + \sqrt{5}) \neq c(h, \omega, N, \sigma, \nu, \lambda)$
III	$\alpha = \infty$	$\Omega_1 = \Omega_2$	(5a)-(5c)	$\kappa_2 \leq c \neq c(h, \omega, N, (\sigma))$
IV	$\alpha = 0$	$\Omega_1 \neq \Omega_2$	(5a)-(5c)	$\kappa_2 \leq c \neq c(h, \omega, N, (\sigma), \Omega_1, \Omega_2)$
V	$\alpha = 0$	$\Omega_1 = \Omega_2$	(5a)-(5d)	$\kappa_2 \leq c \neq c(h, \omega, N, (\sigma), \text{index sets})$
VI	$\alpha = 0$	$\Omega_1 = \Omega_2$	(5a)-(5b) + (5e)	$\kappa_1 \leq c \neq c(h, \omega, N, \sigma, \nu, \lambda, \text{index sets})$

### 3 Numerical validation

The main aim of this paper is to verify the theoretical proven convergence rates by numerical experiments. We consider an academic test problem of the form (1)-(2) or rather (5) in the unit cube  $\Omega = (0, 1)^3$ , and report on various numerical test for various computational settings and varying parameters. Since we are here only interested in the study of the robustness of the solver, it is obviously sufficient to consider the solution of the system corresponding to the block of the mode  $k = 1$ . The numerical results presented in this section were attained using ParMax<sup>3</sup>. We demonstrate the robustness of the block-diagonal preconditioners with respect to the involved parameters. Therefore, for the solution of the preconditioning equations arising from the diagonal blocks, we use the sparse direct solver UMFPACK<sup>4</sup> that is very efficient for several thousand unknowns in the case of three dimensional problems [2,3,4]. For numerical tests, where the diagonal blocks are realized by an auxiliary space preconditioner [6,7], we refer the reader to [10].

#### 3.1 Test case I

Tables 2-5 provide the number of MinRes iterations needed for reducing the initial residual by a factor of  $10^{-8}$ . These experiments demonstrate the independence of the MinRes convergence rate of the parameters  $\omega$ ,  $\sigma$ ,  $\lambda$  and the mesh size  $h$  since the number of iterations is bounded by 28 for all computed constellations. We mention that varying  $\omega$  also covers the variation of  $k\omega$  in terms of  $k$ . Furthermore, in Table 2 and Table 3 we also report the number of unpreconditioned MinRes iterations, that are necessary for reducing the initial residual by a factor of  $10^{-8}$ . The large number of iterations in the unpreconditioned case underline the importance of appropriate preconditioning.

<sup>3</sup> <http://www.numa.uni-linz.ac.at/P19255/software.shtml>

<sup>4</sup> <http://www.cise.ufl.edu/research/sparse/umfpack/>



**Table 2.** Formulation OC-FEM 1 for test case I. Number of MinRes iterations for different values of  $\omega$  and  $\lambda$  using the EXACT version of the preconditioner with UMF-PACK for  $\mathbf{F}$  ( $DOF = 2416$ ,  $\nu = \sigma = 1$ ), [-] number of MinRes iterations without preconditioner.

$\lambda$	$\omega$										
	$10^{-10}$	$10^{-8}$	$10^{-6}$	$10^{-4}$	$10^{-2}$	1	$10^2$	$10^4$	$10^6$	$10^8$	$10^{10}$
$10^{-10}$	7	7	7	7	7	7	7	7	7	6	4
	[587]	[587]	[586]	[587]	[587]	[587]	[587]	[591]	[485]	[263]	[116]
$10^{-6}$	21	21	21	21	21	21	20	12	6	4	4
	[373]	[373]	[373]	[373]	[373]	[373]	[373]	[263]	[116]	[114]	[114]
$10^{-2}$	20	20	20	20	20	20	20	12	6	4	4
	[1134]	[1134]	[1134]	[1136]	[1135]	[1134]	[227]	[114]	[114]	[114]	[114]
1	10	10	10	10	10	14	20	12	6	4	4
	[2349]	[2351]	[2349]	[2350]	[2350]	[2274]	[222]	[114]	[114]	[114]	[114]
$10^2$	6	6	6	6	8	10	20	12	6	4	4
	[2688]	[2681]	[2696]	[2667]	[3291]	[2494]	[224]	[114]	[114]	[114]	[114]
$10^6$	4	4	4	6	6	10	20	12	6	4	4
	[1152]	[1159]	[3434]	[4697]	[4867]	[2493]	[222]	[114]	[114]	[114]	[114]
$10^{10}$	2	4	4	4	4	10	20	12	6	4	4
	[1157]	[1163]	[4937]	[5881]	[4791]	[2501]	[224]	[114]	[114]	[114]	[114]

**Table 3.** Formulation OC-FEM 1 for test case I. Number of MinRes iterations for different values of  $\omega$  and  $\lambda$  using the EXACT version of the preconditioner with UMF-PACK for  $\mathbf{F}$  ( $DOF = 16736$ ,  $\nu = \sigma = 1$ ), [-] number of MinRes iterations without preconditioner. [-] indicates that MinRes did not converge within 10000 iterations.

$\lambda$	$\omega$										
	$10^{-10}$	$10^{-8}$	$10^{-6}$	$10^{-4}$	$10^{-2}$	1	$10^2$	$10^4$	$10^6$	$10^8$	$10^{10}$
$10^{-10}$	9	9	9	9	9	9	9	10	6	4	4
	[708]	[708]	[708]	[708]	[708]	[708]	[708]	[711]	[578]	[308]	[134]
$10^{-6}$	21	21	21	21	21	21	20	18	6	4	4
	[825]	[824]	[825]	[825]	[825]	[825]	[824]	[307]	[134]	[132]	[132]
$10^{-2}$	18	18	18	18	18	20	22	20	6	4	4
	[6698]	[6669]	[6696]	[6698]	[6690]	[6676]	[1095]	[132]	[132]	[132]	[132]
1	10	10	10	10	10	14	22	20	6	4	4
	[-]	[-]	[-]	[-]	[-]	[-]	[1094]	[132]	[132]	[132]	[132]
$10^2$	6	6	6	6	8	10	22	20	6	4	4
	[-]	[-]	[-]	[-]	[-]	[-]	[1094]	[132]	[132]	[132]	[132]
$10^6$	4	4	4	6	6	10	22	20	6	4	4
	[7365]	[7547]	[-]	[-]	[-]	[-]	[1094]	[132]	[132]	[132]	[132]
$10^{10}$	2	4	4	4	4	10	22	20	6	4	4
	[7381]	[1545]	[-]	[-]	[-]	[-]	[1094]	[132]	[132]	[132]	[132]

**Table 4.** Formulation OC-FEM 1 for test case I. Number of MinRes iterations for different values of  $\omega$  and  $\lambda$  using the EXACT version of the preconditioner with UMF-PACK for  $\mathbf{F}$  ( $DOF = 124096$ ,  $\nu = \sigma = 1$ ).

$\lambda$	$\omega$										
	$10^{-10}$	$10^{-8}$	$10^{-6}$	$10^{-4}$	$10^{-2}$	1	$10^2$	$10^4$	$10^6$	$10^8$	$10^{10}$
$10^{-10}$	13	13	13	13	13	13	13	13	8	4	4
$10^{-8}$	21	21	21	21	21	21	21	17	8	4	4
$10^{-6}$	21	21	21	21	21	21	21	20	8	4	4
$10^{-4}$	20	20	20	20	20	20	28	22	8	4	4
$10^{-2}$	16	16	16	16	16	18	22	22	8	4	4
1	10	10	10	10	10	12	20	22	8	4	4
$10^2$	6	6	6	6	8	10	20	22	8	4	4
$10^4$	4	4	4	6	6	10	20	22	8	4	4
$10^6$	4	4	4	4	6	10	20	22	8	4	4
$10^8$	2	4	4	4	6	10	20	22	8	4	4
$10^{10}$	3	4	4	4	4	10	20	22	8	4	4

**Table 5.** Formulation OC-FEM 1 for test case I. Number of MinRes iterations for different values of  $\nu$  and  $\lambda$  using the EXACT version of the preconditioner with UMF-PACK for  $\mathbf{F}$  ( $DOF = 124096$ ,  $\omega = \sigma = 1$ ).

$\lambda$	$\nu$										
	$10^{-10}$	$10^{-8}$	$10^{-6}$	$10^{-4}$	$10^{-2}$	1	$10^2$	$10^4$	$10^6$	$10^8$	$10^{10}$
$10^{-10}$	2	2	3	3	5	13	21	16	6	4	3
$10^{-8}$	2	2	3	4	7	21	20	10	4	4	3
$10^{-6}$	2	3	3	5	13	21	16	6	4	4	4
$10^{-4}$	2	3	4	7	21	20	10	6	4	4	4
$10^{-2}$	3	4	6	13	21	18	8	4	4	6	6
1	4	4	8	17	28	12	6	4	6	6	9
$10^2$	4	4	8	20	22	10	6	4	6	6	8
$10^4$	4	4	8	22	20	10	6	4	4	4	8
$10^6$	4	4	8	22	20	10	4	4	4	4	8
$10^8$	4	4	8	22	20	10	4	4	4	4	8
$10^{10}$	4	4	8	22	20	10	4	2	4	4	8

### 3.2 Test case II

Table 6 and Table 7 provide the number of MinRes iterations needed for reducing the initial residual by a factor  $10^{-8}$ . These experiments demonstrate the independence of the MinRes convergence rate of the parameters  $\omega$ ,  $\sigma$ ,  $\lambda$  and the mesh size  $h$  since the number of iterations is bounded by 88 for all computed constellations.

### 3.3 Test case III

Numerical results for the observation of the magnetic flux density are reported in Table 8-11. The robustness with respect to the space and time discretization parameters  $h$  and  $\omega$  is demonstrated in Table 8. Table 9 and Table 10 describe the non-robust behavior with respect to the parameters  $\lambda$  and  $\nu$ . In Table 11 we observe that for large mesh sizes, good iteration numbers are observed even for small  $\lambda$ . Nevertheless, for fixed  $\lambda$ , the iteration numbers are growing with respect to the involved degrees of freedom.

The next experiment demonstrates, that robustness with respect to the time discretization parameter  $\omega$  cannot be achieved by using the preconditioner  $\mathcal{C}$  in *Formulation OC-FEM 1*. In Table 12 the number of MinRes iteration needed for reducing the initial residual by a factor of  $10^{-8}$  are tabled. In Table 13, the same experiment as in Table 9 is performed, but using *Formulation OC-FEM 1* instead of *Formulation OC-FEM 2*. Indeed, comparing Table 8 with Table 12 and Table 9 with Table 13 clearly shows, that it is essential to work with *Formulation OC-FEM 2*. Beside the robustness with respect to the frequency  $\omega$ , that is related to the time discretization parameters, we additionally observe better iteration numbers with respect to the regularization parameter  $\lambda$  in the interesting region  $0 < \lambda < 1$ .

### 3.4 Test case IV

In this subsection we consider a numerical example with different observation and control domains  $\Omega_1$  and  $\Omega_2$ , i.e.,  $\Omega_1 = \Omega = (0, 1)^3$  and  $\Omega_2 = (0.25, 0.75)^3$ . Let us mention that we have to ensure, that  $\Omega_1$  and  $\Omega_2$  are resolved by the mesh. The corresponding numerical results are documented in Table 14-18. Robustness with respect to the space and time discretization parameters  $h$  and  $\omega$  is demonstrated in Table 14. Table 15 describes the non-robust behavior with respect to the parameters  $\lambda$  and  $\nu$ . Table 16 in combination with Table 18 indicates, that, for the *Formulation OC-FEM 1* in combination with the preconditioner  $\mathcal{C}$ , robustness with respect to the frequency  $\omega$ , that is related to the time discretization parameters, cannot be obtained. Here, we want to mention, that the good iteration numbers observed in Table 16 are caused by the special choice of  $\lambda = 1$ .

**Table 6.** Formulation OC-FEM 2 for test case II. Number of MinRes iterations for different values of  $\omega$  and  $\lambda$  using the EXACT version of the preconditioner with UMFPACK for  $\mathbf{F}$  ( $DOF = 19652$ ,  $\nu = \sigma = 1$ ).

$\lambda$	$\omega$										
	$10^{-10}$	$10^{-8}$	$10^{-6}$	$10^{-4}$	$10^{-2}$	1	$10^2$	$10^4$	$10^6$	$10^8$	$10^{10}$
$10^{-10}$	21	19	19	17	17	17	17	17	12	8	10
$10^{-6}$	33	33	33	33	33	33	29	33	10	8	8
$10^{-2}$	22	22	22	22	26	31	34	32	14	12	10
1	12	13	14	14	14	14	24	22	10	8	8
$10^2$	11	11	13	13	13	18	34	32	14	12	10
$10^6$	13	13	13	17	21	28	56	50	22	14	14
$10^{10}$	31	34	34	23	33	42	80	78	30	20	16

**Table 7.** Formulation OC-FEM 2 for test case II. Number of MinRes iterations for different values of  $\omega$  and  $\lambda$  using the EXACT version of the preconditioner with UMFPACK for  $\mathbf{F}$  ( $DOF = 143748$ ,  $\nu = \sigma = 1$ ).

$\lambda$	$\omega$										
	$10^{-10}$	$10^{-8}$	$10^{-6}$	$10^{-4}$	$10^{-2}$	1	$10^2$	$10^4$	$10^6$	$10^8$	$10^{10}$
$10^{-10}$	27	27	25	25	25	25	25	25	16	8	10
$10^{-6}$	32	32	32	32	32	32	33	35	14	8	8
$10^{-2}$	20	20	20	20	23	29	35	34	16	12	10
1	12	12	14	14	14	14	24	26	12	8	8
$10^2$	11	11	13	13	13	18	34	34	16	12	10
$10^6$	13	13	15	17	21	30	58	60	24	16	14
$10^{10}$	46	61	65	23	33	42	88	88	38	24	16

**Table 8.** Observation of the magnetic flux density  $\mathbf{B}$  in Formulation OC-FEM 2 for test case III. Number of MinRes iterations for different values of  $\omega$  and various DOF using the EXACT version of the preconditioner with UMFPACK for  $\mathbf{F}$  ( $\nu = \sigma = \lambda = 1$ ).

DOF	$\omega$										
	$10^{-10}$	$10^{-8}$	$10^{-6}$	$10^{-4}$	$10^{-2}$	1	$10^2$	$10^4$	$10^6$	$10^8$	$10^{10}$
500	13	13	14	14	14	16	23	12	9	8	7
2916	11	12	13	13	13	15	29	16	10	8	8
19652	11	11	12	12	12	14	30	21	11	8	8
143748	11	11	12	12	12	14	28	27	13	8	8

**Table 9.** Observation of the magnetic flux density  $\mathbf{B}$  in Formulation OC-FEM 2 for test case *III*. Number of MinRes iterations for different values of  $\nu$  and  $\lambda$  using the EXACT version of the preconditioner with UMFPACK for  $\mathbf{F}$  ( $DOF = 19652$ ,  $\sigma = \omega = 1$ ). [-] indicates that MinRes did not converge within 10000 iterations.

$\lambda$	$\nu$										
	$10^{-10}$	$10^{-8}$	$10^{-6}$	$10^{-4}$	$10^{-2}$	1	$10^2$	$10^4$	$10^6$	$10^8$	$10^{10}$
$10^{-10}$	174	175	175	176	175	213	290	68	14	10	8
$10^{-6}$	146	146	146	146	177	215	58	12	8	6	8
$10^{-2}$	272	272	272	289	306	55	13	10	9	10	13
1	290	290	290	292	240	14	8	6	8	10	12
$10^2$	475	474	479	448	83	18	12	10	14	14	26
$10^6$	193	193	195	179	55	28	18	24	24	26	360
$10^{10}$	36	38	39	77	84	42	26	36	50	264	[-]

**Table 10.** Observation of the magnetic flux density  $\mathbf{B}$  in Formulation OC-FEM 2 for test case *III*. Number of MinRes iterations for different values of  $\nu$  and  $\lambda$  using the EXACT version of the preconditioner with UMFPACK for  $\mathbf{F}$  ( $DOF = 143748$ ,  $\sigma = \omega = 1$ ). [-] indicates that MinRes did not converge within 10000 iterations.

$\lambda$	$\nu$										
	$10^{-10}$	$10^{-8}$	$10^{-6}$	$10^{-4}$	$10^{-2}$	1	$10^2$	$10^4$	$10^6$	$10^8$	$10^{10}$
$10^{-10}$	325	324	326	326	327	411	505	65	14	10	8
$10^{-6}$	289	289	289	289	359	392	53	12	10	6	8
$10^{-2}$	543	543	543	561	523	52	13	10	8	11	15
1	543	544	541	564	325	14	8	6	8	10	14
$10^2$	948	949	941	861	79	18	12	10	14	14	36
$10^6$	688	688	680	377	55	30	18	22	26	40	[-]
$10^{10}$	56	56	55	91	88	42	26	38	54	[-]	[-]

**Table 11.** Observation of the magnetic flux density  $\mathbf{B}$  in Formulation OC-FEM 2 for test case *III*. Number of MinRes iterations for different values of  $\lambda$  and various DOF using the EXACT version of the preconditioner with UMFPACK for  $\mathbf{F}$  ( $\nu = \sigma = \omega = 1$ ).

DOF	$\lambda$										
	$10^{-10}$	$10^{-8}$	$10^{-6}$	$10^{-4}$	$10^{-2}$	1	$10^2$	$10^4$	$10^6$	$10^8$	$10^{10}$
500	36	36	37	39	40	16	19	26	30	36	44
2916	115	113	121	121	55	15	18	24	28	38	44
19652	213	214	215	195	55	14	18	24	28	36	42
143748	411	402	392	265	52	14	18	24	30	36	42

**Table 12.** Observation of the magnetic flux density  $\mathbf{B}$  in Formulation OC-FEM 1 for test case *III*. Number of MinRes iterations for different values of  $\omega$  and various DOF using the EXACT version of the preconditioner with UMFPACK for  $\mathbf{F}$  ( $\nu = \sigma = \lambda = 1$ ). [-] indicates that MinRes did not converge within 10000 iterations.

DOF	$\omega$										
	$10^{-10}$	$10^{-8}$	$10^{-6}$	$10^{-4}$	$10^{-2}$	1	$10^2$	$10^4$	$10^6$	$10^8$	$10^{10}$
392	4133	[-]	46	20	16	15	21	9	5	4	3
2416	[-]	[-]	64	29	15	13	27	12	6	4	4
16736	[-]	[-]	102	28	15	13	26	18	7	4	4
124096	[-]	[-]	28	13	12	26	24	9	5	4	4

**Table 13.** Observation of the magnetic flux density  $\mathbf{B}$  in Formulation OC-FEM 1 for test case *III*. Number of MinRes iterations for different values of  $\nu$  and  $\lambda$  using the EXACT version of the preconditioner with UMFPACK for  $\mathbf{F}$  ( $DOF = 16736$ ,  $\sigma = \omega = 1$ ). [-] indicates that MinRes did not converge within 10000 iterations.

$\lambda$	$\nu$										
	$10^{-10}$	$10^{-8}$	$10^{-6}$	$10^{-4}$	$10^{-2}$	1	$10^2$	$10^4$	$10^6$	$10^8$	$10^{10}$
$10^{-10}$	739	901	1073	1140	1462	1153	1548	182	32	19	[-]
$10^{-6}$	357	361	357	385	478	607	96	17	10	9	18
$10^{-2}$	234	234	234	253	279	50	9	6	7	6	9
1	260	260	260	259	214	13	7	5	6	6	8
$10^2$	462	462	469	440	76	11	6	4	6	6	7
$10^6$	79	79	79	73	21	10	4	4	4	4	6
$10^{10}$	10	10	9	19	22	10	4	3	4	4	6

**Table 14.** Different control and observation domains in Formulation OC-FEM 2 for test case *IV*. Number of MinRes iterations for different values of  $\omega$  and various DOF using the EXACT version of the preconditioner with UMFPACK for  $\mathbf{F}$  ( $\nu = \sigma = \lambda = 1$ ).

DOF	$\omega$										
	$10^{-10}$	$10^{-8}$	$10^{-6}$	$10^{-4}$	$10^{-2}$	1	$10^2$	$10^4$	$10^6$	$10^8$	$10^{10}$
2916	19	19	20	21	23	30	30	22	12	8	8
19652	19	19	20	21	24	30	32	26	12	8	8
143748	19	19	19	21	23	29	32	28	14	10	8

**Table 15.** Different control and observation domains in Formulation OC-FEM 2 for test case IV. Number of MinRes iterations for different values of  $\nu$  and  $\lambda$  using the EXACT version of the preconditioner with UMFPACK for  $\mathbf{F}$  ( $DOF = 19652$ ,  $\sigma = \omega = 1$ ). [-] indicates that MinRes did not converge within 10000 iterations.

$\lambda$	$\nu$										
	$10^{-10}$	$10^{-8}$	$10^{-6}$	$10^{-4}$	$10^{-2}$	1	$10^2$	$10^4$	$10^6$	$10^8$	$10^{10}$
$10^{-10}$	1038	1006	661	3421	[-]	[-]	[-]	946	49	28	9
$10^{-6}$	342	344	363	843	6843	7142	619	256	26	9	8
$10^{-2}$	188	206	209	313	607	204	114	82	79	80	106
1	40	40	41	48	52	30	26	26	26	24	26
$10^2$	41	41	42	64	70	40	26	22	22	20	28
$10^6$	24	24	30	68	76	38	24	16	26	42	414
$10^{10}$	22	22	34	88	148	46	44	36	68	276	[-]

**Table 16.** Different control and observation domains in Formulation OC-FEM 1 for test case IV. Number of MinRes iterations for different values of  $\omega$  and various DOF using the EXACT version of the preconditioner with UMFPACK for  $\mathbf{F}$  ( $\nu = \sigma = \lambda = 1$ ). [-] indicates that MinRes did not converge within 10000 iterations.

DOF	$\omega$										
	$10^{-10}$	$10^{-8}$	$10^{-6}$	$10^{-4}$	$10^{-2}$	1	$10^2$	$10^4$	$10^6$	$10^8$	$10^{10}$
2416	34	34	67	61	52	30	22	12	6	4	4
16736	32	33	82	67	51	30	22	20	6	4	4
124096	29	31	83	63	48	30	20	22	8	4	4

**Table 17.** Different control and observation domains in Formulation OC-FEM 1 for test case IV. Number of MinRes iterations for different values of  $\nu$  and  $\lambda$  using the EXACT version of the preconditioner with UMFPACK for  $\mathbf{F}$  ( $DOF = 16736$ ,  $\sigma = \omega = 1$ ). [-] indicates that MinRes did not converge within 10000 iterations.

$\lambda$	$\nu$										
	$10^{-10}$	$10^{-8}$	$10^{-6}$	$10^{-4}$	$10^{-2}$	1	$10^2$	$10^4$	$10^6$	$10^8$	$10^{10}$
$10^{-10}$	34	34	36	66	2701	[-]	983	103	60	47	[-]
$10^{-6}$	31	32	32	87	2630	828	81	46	41	58	73
$10^{-2}$	29	37	37	66	169	61	43	39	37	43	47
1	19	20	22	29	39	30	25	23	22	21	24
$10^2$	10	10	11	20	22	13	12	12	11	10	10
$10^6$	6	6	6	20	22	10	6	6	6	6	6
$10^{10}$	4	4	6	20	22	10	4	4	4	4	6

**Table 18.** Different control and observation domains in Formulation OC-FEM 1 for test case IV. Number of MinRes iterations for different values of  $\omega$  and  $\lambda$  using the EXACT version of the preconditioner with UMFPACK for  $\mathbf{F}$  ( $DOF = 16736$ ,  $\sigma = \nu = 1$ ). [-] indicates that MinRes did not converge within 10000 iterations.

$\lambda$	$\omega$										
	$10^{-10}$	$10^{-8}$	$10^{-6}$	$10^{-4}$	$10^{-2}$	1	$10^2$	$10^4$	$10^6$	$10^8$	$10^{10}$
$10^{-10}$	9338	9347	9346	9340	[-]	[-]	2630	66	11	6	4
$10^{-6}$	571	571	571	1075	983	828	169	20	6	4	4
$10^{-2}$	49	49	122	103	81	61	22	20	6	4	4
1	32	33	82	67	51	30	22	20	6	4	4
$10^2$	23	112	60	46	43	13	22	20	6	4	4
$10^6$	[-]	46	41	39	12	10	22	20	6	4	4
$10^{10}$	[-]	58	37	12	6	10	22	20	6	4	4

### 3.5 Test case VI

Numerical results for the case of state constraints imposed on the Fourier coefficients are presented in Table 19-20. Here we choose 15512 random points as the active sets  $\mathcal{E}^c$  and  $\mathcal{E}^s$  and solve the resulting Jacobi system. The dependence of the MinRes convergence rate on the Moreau-Yosida regularization parameter  $\varepsilon$  is demonstrated in Table 19 and Table 20. Table 21 clearly demonstrates the robustness with respect to the parameters  $\lambda$  and  $\omega$ . We refer the reader to [11] for a detailed description of the treatment of state constraints via the Moreau-Yosida regularization. Furthermore, we mention that the presence of constraints imposed on the control Fourier coefficients finally results in (linearized) systems with system matrices having the same structure as the system matrix arising from the case of different observation and control domains.

## 4 Summary and Conclusion

We demonstrated in many numerical experiments that the preconditioners derived and analysed in [12] and [11] lead to parameter-robust and efficient solvers in many practically important cases. Therefore, we reported on a broad range of numerical experiments, that confirm the theoretical convergence rates. Consequently, the multiharmonic finite element discretization technique in combination with efficient and parameter-robust solvers leads to a very competitive method. Furthermore, we want to mention, that due to the decoupling nature of the frequency domain equations with respect to the individual modes, a parallelization of the proposed method is straightforward, cf. Algorithm 1.



**Table 19.** State constraints in Formulation OC-FEM 1 for test case VI. Number of MinRes iterations for different values of  $\varepsilon$  and  $\lambda$  using the EXACT version of the preconditioner with UMFPACK for  $\mathbf{F}$  ( $DOF = 16736$ ,  $\nu = \sigma = \omega = 1$ ). [-] indicates that MinRes did not converge within 10000 iterations.

$\lambda$	$\varepsilon$										
	$10^{-10}$	$10^{-8}$	$10^{-6}$	$10^{-4}$	$10^{-2}$	1	$10^2$	$10^4$	$10^6$	$10^8$	$10^{10}$
$10^{-10}$	88	74	59	45	31	17	9	9	9	9	9
$10^{-6}$	992	801	612	421	220	36	21	21	21	21	21
$10^{-2}$	[-]	[-]	[-]	3259	351	29	20	20	20	20	20
1	[-]	[-]	[-]	3795	191	24	16	16	14	14	14
$10^2$	[-]	[-]	[-]	1619	120	13	12	10	10	10	10
$10^6$	[-]	[-]	5852	160	12	10	10	10	10	10	10
$10^{10}$	[-]	7681	162	12	10	10	10	10	10	10	10

**Table 20.** State constraints in Formulation OC-FEM 1 for test case VI. Number of MinRes iterations for different values of  $\varepsilon$  and  $\lambda$  using the EXACT version of the preconditioner with UMFPACK for  $\mathbf{F}$  ( $DOF = 124096$ ,  $\nu = \sigma = \omega = 1$ ). [-] indicates that MinRes did not converge within 10000 iterations.

$\lambda$	$\varepsilon$										
	$10^{-10}$	$10^{-8}$	$10^{-6}$	$10^{-4}$	$10^{-2}$	1	$10^2$	$10^4$	$10^6$	$10^8$	$10^{10}$
$10^{-10}$	142	118	94	70	46	22	13	13	13	13	13
$10^{-6}$	3275	2602	1930	1241	372	35	21	21	21	21	21
$10^{-2}$	[-]	[-]	[-]	5482	383	29	18	18	18	18	18
1	[-]	[-]	[-]	5443	206	24	16	14	13	12	12
$10^2$	[-]	[-]	[-]	1836	124	13	12	10	10	10	10
$10^6$	[-]	[-]	6619	167	11	10	10	10	10	10	10
$10^{10}$	[-]	8883	167	11	10	10	10	10	10	10	10

**Table 21.** State constraints in Formulation OC-FEM 1 for test case VI. Number of MinRes iterations for different values of  $\omega$  and  $\lambda$  using the EXACT version of the preconditioner with UMFPACK for  $\mathbf{F}$  ( $DOF = 124096$ ,  $\nu = \sigma = \varepsilon = 1$ ).

$\lambda$	$\omega$										
	$10^{-10}$	$10^{-8}$	$10^{-6}$	$10^{-4}$	$10^{-2}$	1	$10^2$	$10^4$	$10^6$	$10^8$	$10^{10}$
$10^{-10}$	22	22	22	22	22	22	22	22	12	6	4
$10^{-6}$	35	35	35	35	35	35	35	22	8	4	4
$10^{-2}$	30	30	30	30	30	29	22	22	8	4	4
1	20	20	20	20	20	24	20	22	8	4	4
$10^2$	16	16	16	16	18	13	20	22	8	4	4
$10^6$	13	13	14	18	12	10	20	22	8	4	4
$10^{10}$	13	13	16	12	6	10	20	22	8	4	4

## Acknowledgements

The authors gratefully acknowledge the financial support by the Austrian Science Fund (FWF) under the grants P19255 and W1214 (project DK04). The authors also thank the Austria Center of Competence in Mechatronics (ACCM), which is a part of the COMET K2 program of the Austrian Government, for supporting their work on eddy current problems.

## References

1. D. Abbeloos, M. Diehl, M. Hinze, and S. Vandewalle. Nested multigrid methods for time-periodic, parabolic optimal control problems. *Computing and Visualization in Science*, 14(1):27–38, 2011.
2. T.A. Davis. Algorithm 832: Umfpack v4.3—an unsymmetric-pattern multifrontal method. *ACM Trans. Math. Softw.*, 30:196–199, June 2004.
3. T.A. Davis. A column pre-ordering strategy for the unsymmetric-pattern multifrontal method. *ACM Trans. Math. Softw.*, 30:165–195, June 2004.
4. T.A. Davis and I.S. Duff. A combined unifrontal/multifrontal method for unsymmetric sparse matrices. *ACM Trans. Math. Softw.*, 25:1–20, March 1999.
5. M. Hintermüller, K. Ito, and K. Kunisch. The primal-dual active set strategy as a semismooth Newton method. *SIAM J. Optim.*, 13(3):865–888, 2002.
6. R. Hiptmair and J. Xu. Nodal auxiliary space preconditioning in  $\mathbf{H}(\mathbf{curl})$  and  $\mathbf{H}(\mathbf{div})$  spaces. *SIAM J. Numer. Anal.*, 45(6):2483–2509, 2007.
7. T.V. Kolev and P.S. Vassilevski. Parallel auxiliary space AMG for  $H(\mathbf{curl})$  problems. *J. Comput. Math.*, 27(5):604–623, 2009.
8. M. Kollmann and M. Kolmbauer. A preconditioned MinRes solver for time-periodic parabolic optimal control problems. *Numerical Linear Algebra with Applications*, 2012. doi: 10.1002/nla.1842.
9. M. Kollmann, M. Kolmbauer, U. Langer, M. Wolfmayr, and W. Zulehner. A finite element solver for a multiharmonic parabolic optimal control problem. *Computers and Mathematics with Applications*, 2012. doi: 10.1016/j.camwa-2012.06.012.
10. M. Kolmbauer. *The Multiharmonic Finite Element and Boundary Element Method for Simulation and Control of Eddy Current Problems*. PhD thesis, Johannes Kepler University, Institute of Computational Mathematics, Linz, Austria, 2012.
11. M. Kolmbauer. Efficient solvers for multiharmonic eddy current optimal control problems with various constraints and their analysis. *IMA J. Numer. Anal.*, 2012. (to appear).
12. M. Kolmbauer and U. Langer. A robust preconditioned MinRes solver for distributed time-periodic eddy current optimal control problems. *SIAM Journal on Scientific Computing*, 2012. (to appear).
13. C.C. Paige and M.A. Saunders. Solutions of sparse indefinite systems of linear equations. *SIAM J. Numer. Anal.*, 12(4):617–629, 1975.
14. F. Tröltzsch. *Optimal Control of Partial Differential Equations. Theory, Methods and Applications*. Graduate Studies in Mathematics 112, AMS, Providence, 2010.
15. F. Tröltzsch and I. Yousept. PDE-constrained optimization of time-dependent 3D electromagnetic induction heating by alternating voltages. *ESAIM: M2AN*, 46:709–729, 2012.
16. I. Yousept. Optimal control of Maxwell’s equations with regularized state constraints. *Computational Optimization and Applications*, 52(2):559–581, 2012.

## Latest Reports in this series

### 2009 - 2010

[..]

### 2011

[..]

- 2011-06 Markus Kollmann and Michael Kolmbauer  
*A Preconditioned MinRes Solver for Time-Periodic Parabolic Optimal Control Problems* August 2011
- 2011-07 Nicole Spillane, Victorita Dolean, Patrice Hauret, Frédéric Nataf, Clemens Pechstein and Robert Scheichl  
*Abstract Robust Coarse Spaces for Systems of PDEs via Generalized Eigenproblems in the Overlaps* November 2011
- 2011-08 Michael Kolmbauer  
*A Robust FEM-BEM MinRes Solver for Distributed Multiharmonic Eddy Current Optimal Control Problems in Unbounded Domains* November 2011
- 2011-09 Michael Kolmbauer  
*Efficient Solvers for Multiharmonic Eddy Current Optimal Control Problems with Various Constraints* November 2011
- 2011-10 Markus Kollmann, Michael Kolmbauer, Ulrich Langer, Monika Wolfmayr and Walter Zulehner  
*A Finite Element Solver for a Multiharmonic Parabolic Optimal Control Problem* December 2011

### 2012

- 2012-01 Markus Kollmann and Walter Zulehner  
*A Robust Preconditioner for Distributed Optimal Control for Stokes Flow with Control Constraints* January 2012
- 2012-02 Michael Kolmbauer and Ulrich Langer  
*A Robust Preconditioned MinRes-Solver for Time-Periodic Eddy Current Problems* January 2012
- 2012-03 Wolfgang Krendl, Valeria Simoncini and Walter Zulehner  
*Stability Estimates and Structural Spectral Properties of Saddle Point Problems* February 2012
- 2012-04 Helmut Gfrerer  
*On Directional Metric Regularity, Subregularity and Optimality Conditions for Nonsmooth Mathematical Programs* February 2012
- 2012-05 Veronika Pillwein and Stefan Takacs  
*A Multigrid Fourier Analysis of a Multigrid Method using Symbolic Computation* April 2012
- 2012-06 Stefan Takacs and Walter Zulehner  
*Convergence Analysis of All-at-once Multigrid Methods for Elliptic Control Problems Under Partial Elliptic Regularity* June 2012
- 2012-07 Helmut Gfrerer  
*On Directional Metric Subregularity and Second-Order Optimality Conditions for a Class of Nonsmooth Mathematical Programs* August 2012
- 2012-08 Michael Kolmbauer and Ulrich Langer  
*Efficient Solvers for Some Classes of Time-Periodic Eddy Current Optimal Control Problems* November 2012

From 1998 to 2008 reports were published by SFB013. Please see

<http://www.sfb013.uni-linz.ac.at/index.php?id=reports>

From 2004 on reports were also published by RICAM. Please see

<http://www.ricam.oeaw.ac.at/publications/list/>

For a complete list of NuMa reports see

<http://www.numa.uni-linz.ac.at/Publications/List/>